

Blindkupplungen mit Kette Blank Caps with chain



Dichtung: Nitril-Kautschuk schwarz / weiß
Viton Dichtung bei V4A

Seal: Nitrile rubber black / white
Fluoro rubber - Stainless steel



Aluminium light alloy	Messing copper alloy	Edelstahl stainless steel
--------------------------	-------------------------	------------------------------

Storz Size	KA (mm) Lug	Weight (kg)	Bemerkung Remark	Ident-No.	Euro
25-D	31	0,09	DIN 14 310	31-031000-10	
		0,26		31-031000-30	
		0,25		31-031000-43	
32	44	0,13		31-044000-10	
		0,37		31-044000-30	
38	51	0,17		31-051000-10	
		0,50		31-051000-30	
		0,50		31-051000-43	
45	59	0,30		31-059000-10	
52-C	66	0,38	DIN 14 311	31-066000-10	
		0,34	gegossen / cast *	31-066000-21	
		0,92	DIN 86 206	31-066000-30	
		0,88		31-066000-43	
65	81	0,46		31-081000-10	
		1,27		31-081000-30	
		1,27		31-081000-43	
75-B	89	0,56	DIN 14 312	31-089000-10	
		0,52	gegossen / cast *	31-089000-21	
		1,46	DIN 86 207	31-089000-30	
		1,34		31-089000-43	
90	105	0,82		31-105000-10	
100	115	0,96		31-115000-10	
		2,93		31-115000-30	
		2,74		31-115000-43	
110-A	133	1,34	DIN 14 313	31-133000-10	
		1,20	gegossen / cast *	31-133000-21	
		3,73		31-133000-30	
		3,65		31-133000-43	

Blindkupplungen mit Kette
Blank Caps with chain



Storz Size	KA (mm) Lug	Weight (kg)	Bemerkung Remark	Ident-No.	Euro
125	148	1,70		31-148000-10	
		4,90		31-148000-30	
		4,61		31-148000-43	
150	160	2,14		31-160000-10	
		7,60		31-160000-30	
		7,13		31-160000-43	
205	220	3,95	max. PN 10 bar	31-220000-10	
250	278	8,94	max. PN 10 bar	31-278000-10	

* Industriekupplung PN 6 (siehe Seite 61) - *industrial coupling PN 6 (see page 61)*