

# EMW 80T

**Motopompa autoadescente per acque sporche**  
Dirty water self-priming motor pump  
Moto-pompe auto-amorçante pour eaux chargées



## CARATTERISTICHE: SPECIFICATIONS: CARACTÉRISTIQUES:

|   |                            |
|---|----------------------------|
| <b>Motore Stage V - 4 tempi</b><br>Engine Stage v - 4stroke<br>Moteur Stage V - 4 temps                     | <b>R210</b>                |
| <b>Cilindrata</b><br>Displacement<br>Déplacement  | <b>212 cc</b>              |
| <b>Sistema di avviamento</b><br>Starting system<br>Système de démarrage                                     | <b>A strappo</b><br>Recoil |
| <b>Portata di aspirazione e scarico</b><br>Suction & discharge port<br>Porte d'aspiration et de refoulement | <b>80 mm</b>               |
| <b>Aspirazione massima</b><br>Max suction head lift<br>Hauteur maximale d'aspiration                        | <b>7 m</b>                 |
| <b>Pressione massima</b><br>Max head lift<br>Pression maximale  | <b>26 m</b>                |

|   |                                       |
|---|---------------------------------------|
| <b>Carburante</b><br>Fuel<br>Carburant  | <b>Benzina</b><br>Gasoline<br>Essence |
| <b>Capacità mandata</b><br>Discharge capacity<br>Capacité maximale                      | <b>1100 L/min</b>                     |
| <b>Consumo di carburante</b><br>Fuel consumption<br>Consommation de carburant           | <b>≤395 g/Kwh</b>                     |
| <b>Dimensioni</b><br>Dimensions<br>Dimensions   | <b>552x432x450 mm</b>                 |
| <b>Peso</b><br>Weight<br>Poids  | <b>35 Kg</b>                          |
| <b>Passaggio corpi solidi</b><br>Solids handling<br>Passage de corps solides            | <b>25,4 mm</b>                        |
| <b>Corpo pompa ispezionabile</b><br>Inspectable pump body<br>Corps de pompe inspectable | <b>Yes</b>                            |